

ESH 300 F Trend GB

FLOOR MOUNTED CYLINDER

PRODUCT-NO.: 204796

The main features

High DHW convenience due to electric flanged immersion heaters

Durable and lightweight inner cylinder made from stainless steel

Low energy losses thanks to the high grade thermal insulation

Straightforward installation due to low weight, pre-installed components and height-adjustable feet

Space saving installation possible with optional mounting bracket – for example above the washing machine



ESH 120 F Trend GB
Product-No.: 204791



ESH 150 F Trend GB
Product-No.: 204792



ESH 180 F Trend GB
Product-No.: 204793



ESH 210 F Trend GB
Product-No.: 204794



ESH 250 F Trend GB
Product-No.: 204795



| Type | ESH 120 F Trend GB | ESH 150 F Trend GB | ESH 180 F Trend GB |
|----------|--------------------|--------------------|--------------------|
| Part no. | 204791 | 204792 | 204793 |

Technical data

| | | | |
|--|--------------------|----------------|--------------------|
| Power supply | 1/N/PE ~ 220-240 V | 1/N/PE | 1/N/PE ~ 220-240 V |
| Rated voltage | 240 V | 240 V | 240 V |
| Load profile | L | L | XL |
| Energy efficiency class | C | C | C |
| Standby energy consumption/24 h at 65 °C | 1.03 kWh | 1.27 kWh | 1.42 kWh |
| Nominal capacity | 111 l | 143 l | 164 l |
| Mixed water amount at 40 °C | 152 l | 183,7 l | 209,2 l |
| Temperature setting range | 30-60 °C | 30-60 °C | 30-60 °C |
| Max. flow rate | 15 l/min | 15 l/min | 15 l/min |
| Flanged immersion heater version | Single circuit | Single circuit | Single circuit |
| Colour | white | white | white |
| IP rating | IP 21 | IP 21 | IP 21 |
| Height | 870 mm | 1050 mm | 1160 mm |
| Width | 575 mm | 575 mm | 575 mm |
| Depth | 575 mm | 575 mm | 575 mm |
| Weight, empty | 37 kg | 42 kg | 47 kg |



| | | | |
|----------|--------------------|--------------------|--------------------|
| Type | ESH 210 F Trend GB | ESH 250 F Trend GB | ESH 300 F Trend GB |
| Part no. | 204794 | 204795 | 204796 |

Technical data

| | | | |
|--|--------------------|--------------------|--------------------|
| Power supply | 1/N/PE ~ 220-240 V | 1/N/PE ~ 220-240 V | 1/N/PE ~ 220-240 V |
| Rated voltage | 240 V | 240 V | 240 V |
| Load profile | XL | XL | XL |
| Energy efficiency class | C | C | D |
| Standby energy consumption/24 h at 65 °C | 1.56 kWh | 1.75 kWh | 2.04 kWh |
| Nominal capacity | 193 l | 242 l | 280 l |
| Mixed water amount at 40 °C | 275,3 l | 332,6 l | 384,2 l |
| Temperature setting range | 30-60 °C | 30-60 °C | 30-60 °C |
| Max. flow rate | 15 l/min | 15 l/min | 15 l/min |
| Flanged immersion heater version | Single circuit | Single circuit | Single circuit |
| Colour | white | white | white |
| IP rating | IP 21 | IP 21 | IP 21 |
| Height | 1300 mm | 1550 mm | 1750 mm |
| Width | 575 mm | 575 mm | 575 mm |
| Depth | 575 mm | 575 mm | 575 mm |
| Weight, empty | 52 kg | 59 kg | 65 kg |

Contact information

Do you have additional questions? Then please do not hesitate to contact us, we would be only too happy to help:

Call 0151 346 2300

Or send an e-mail to

sales@stiebel-eltron.co.uk

Only a qualified contractor should carry out the installation, commissioning, maintenance and repair of this appliance. Where applicable and prior to installation the electricity and/or water utility companies should be notified of your intention to install the product.